

Standard toroidal transformers, 58-XXX-XXX-x Series
Power: 12 VA - 800 VA

Primary: 230 V

 "x" in part number denotes [mounting styles](#) (S, B, H, or D)

Output [VA]	Part number	Prim. load [V]	Sek. load [V]	Sek. current [A]	Open circuit [V]	Dimensions (p x v / hm) [mm/kg]	fuse (sek.) [A]
12	58-0012-012-x	230	12	1,000	13,96	57x29 / 0,26	1,00
	58-0012-018-x	230	18	0,667	20,83		0,63
	58-0012-024-x	230	24	0,500	27,92		0,50
	58-0012-030-x	230	30	0,400	34,94		0,40
20	58-0020-012-x	230	12	1,667	13,96	57x35 / 0,35	1,60
	58-0020-018-x	230	18	1,111	20,85		1,25
	58-0020-024-x	230	24	0,833	27,64		1,00
	58-0020-030-x	230	30	0,667	34,53		0,63
32	58-0032-012-x	230	12	2,667	13,96	70x36 / 0,48	2,50
	58-0032-018-x	230	18	1,778	20,85		2,00
	58-0032-024-x	230	24	1,333	27,64		1,60
	58-0032-030-x	230	30	1,067	34,62		1,00
50	58-0050-012-x	230	12	4,167	13,70	80x33 / 0,63	4,00
	58-0050-018-x	230	18	2,778	20,60		3,15
	58-0050-024-x	230	24	2,083	27,28		2,00
	58-0050-030-x	230	30	1,667	34,18		1,60
	58-0050-048-x	230	48	1,042	54,67		1,00
	58-0050-060-x	230	60	0,833	68,14		0,80
	58-0050-115-x	230	115	0,435	129,94		0,50
80	58-0080-012-x	230	12	6,667	13,38	80x44 / 0,89	6,30
	58-0080-018-x	230	18	4,444	20,16		5,00
	58-0080-024-x	230	24	3,333	26,76		3,15
	58-0080-030-x	230	30	2,667	33,37		2,50
	58-0080-048-x	230	48	1,667	53,35		1,60
	58-0080-060-x	230	60	1,333	66,73		1,25
	58-0100-012-x	230	12	8,333	13,56		93x42 / 1,1
58-0100-018-x	230	18	5,556	20,48	6,30		
58-0100-024-x	230	24	4,167	27,27	4,00		
58-0100-030-x	230	30	3,333	34,05	3,15		
58-0100-048-x	230	48	2,083	54,39	2,00		
58-0100-060-x	230	60	1,667	67,96	1,60		
58-0100-115-x	230	115	0,870	128,85	1,00		
58-0100-230-x	230	230	0,435	257,97	0,50		
125	58-0125-012-x	230	12	10,417	13,40	94x46 / 1,2	10,00
	58-0125-018-x	230	18	6,944	20,02		8,00
	58-0125-024-x	230	24	5,210	26,80		5,00
	58-0125-030-x	230	30	4,167	33,58		4,00
	58-0125-048-x	230	48	2,604	53,60		2,50
	58-0125-060-x	230	60	2,083	67,00		2,00
	58-0160-012-x	230	12	13,333	13,18		99x51 / 1,5
58-0160-018-x	230	18	8,889	19,87	10,00		
58-0160-024-x	230	24	6,667	26,35	6,30		
58-0160-030-x	230	30	5,333	33,05	5,00		
58-0160-048-x	230	48	3,333	52,70	3,15		
58-0160-060-x	230	60	2,667	65,87	2,50		

200	58-0200-012-x	230	12	16,667	13,05	115x49 / 1,9	16,00
	58-0200-018-x	230	18	11,111	19,58		12,50
	58-0200-024-x	230	24	8,333	26,11		8,00
	58-0200-030-x	230	30	6,667	32,63		6,30
	58-0200-048-x	230	48	4,167	52,44		4,00
	58-0200-060-x	230	60	3,333	65,04		3,15
	58-0200-115-x	230	115	1,739	124,23		2,00
	58-0200-230-x	230	230	0,870	246,65		1,00
250	58-0250-012-x	230	12	20,833	13,00	117x54 / 2,2	20,00
	58-0250-018-x	230	18	13,889	19,63		16,00
	58-0250-024-x	230	24	10,417	26,01		10,00
	58-0250-030-x	230	30	8,333	32,38		8,00
	58-0250-048-x	230	48	5,208	52,02		5,00
	58-0250-060-x	230	60	4,167	64,77		4,00
300	58-0300-012-x	230	12	25,000	13,04	117x61 / 2,5	25,00
	58-0300-018-x	230	18	16,667	19,56		16,00
	58-0300-024-x	230	24	12,500	26,08		12,50
	58-0300-030-x	230	30	10,000	32,31		10,00
	58-0300-048-x	230	48	6,250	51,87		6,30
	58-0300-060-x	230	60	5,000	64,32		5,00
	58-0300-115-x	230	115	2,609	122,71		3,15
400	58-0400-012-x	230	12	33,333	12,64	137x54 / 3,2	35,00
	58-0400-024-x	230	24	16,667	25,59		16,00
	58-0400-030-x	230	30	13,333	31,91		12,50
	58-0400-048-x	230	48	8,333	51,18		8,00
	58-0400-060-x	230	60	6,667	64,14		6,30
	58-0400-230-x	230	230	1,739	242,64		2,00
500	58-0500-012-x	230	12	41,667	12,61	140x64 / 3,9	50,00
	58-0500-030-x	230	30	16,667	31,90		16,00
	58-0500-048-x	230	48	10,417	50,82		10,00
	58-0500-060-x	230	60	8,333	63,44		8,00
630	58-0630-048-x	230	48	13,125	50,34	164x58 / 4,9	12,50
	58-0630-060-x	230	60	10,500	63,03		10,00
800	58-0800-048-x	230	48	16,667	50,17	166x67 / 6,0	16,00
	58-0800-060-x	230	60	13,333	62,94		12,50