



Glass Passivated Power Voltage-Regulating Diodes



DO-204AL (DO-41)

FEATURES

- Plastic MELF package
- Ideal for automated placement
- Glass passivated chip junction
- Low Zener impedance
- Low regulation factor
- Solder dip 275 °C max. 10 s, per JESD 22-B106
- AEC-Q101 qualified
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912



RoHS COMPLIANT

| PRIMARY CHARACTERISTICS | |
|-------------------------|----------------|
| V_Z | 100 V to 200 V |
| P_{tot} | 1500 mW |
| $I_R (V_Z \geq 12 V)$ | 5.0 μA |
| T_J max. | 150 °C |
| V_Z specification | Pulse current |
| Int. construction | Single |

MECHANICAL DATA

Case: DO-204AL (DO-41)

Molding compound meets UL 94 V-0 flammability rating
Base P/N-E3 - RoHS-compliant, commercial grade
Base P/NHE3 - RoHS-compliant, AEC-Q101 qualified

Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3 suffix meets JESD 201 class 1A whisker test, HE3 suffix meets JESD 201 class 2 whisker test

Polarity: Color band denotes cathode end

TYPICAL APPLICATIONS

For general purpose regulation and protection applications.

| MAXIMUM RATINGS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) | | | |
|--|----------------|---------------|------|
| PARAMETER | SYMBOL | VALUE | UNIT |
| Operating junction and storage temperature range | T_J, T_{STG} | - 55 to + 150 | °C |



| ELECTRICAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) | | | | | | | | | | | | |
|--|---------------------|------|------|--------------|----------|-------------------------|----------------------|-------------------------|--------|-------|------------------------------------|-----------------------|
| PART NUMBER ⁽¹⁾ | ZENER VOLTAGE RANGE | | | TEST CURRENT | | MAXIMUM ZENER IMPEDANCE | | MAXIMUM REVERSE CURRENT | | | MAXIMUM CONTINUOUS FORWARD VOLTAGE | MAXIMUM ZENER CURRENT |
| | V_Z at I_{ZT} | | | I_{ZT} | I_{ZK} | Z_{ZT} at I_{ZT} | Z_{ZK} at I_{ZK} | I_R at V_R | | | V_{FM} at 0.5 A | I_{ZM} |
| | V | | | mA | | Ω | | μA | V | | V | mA |
| | MIN. | NOM. | MAX. | | | MAX. | MAX. | 25 °C | 100 °C | | MAX. | MAX. |
| Z4KE100A | 95 | 100 | 105 | 5.0 | 0.25 | 500 | 5000 | 0.5 | 100 | 76.0 | 1.0 | 15.0 |
| Z4KE110A | 104 | 110 | 116 | 5.0 | 0.25 | 600 | 5000 | 0.5 | 100 | 83.2 | 1.0 | 13.0 |
| Z4KE120A | 114 | 120 | 126 | 5.0 | 0.25 | 700 | 5000 | 0.5 | 100 | 91.2 | 1.0 | 12.0 |
| Z4KE130A | 124 | 130 | 137 | 5.0 | 0.25 | 800 | 5000 | 0.5 | 100 | 99.2 | 1.0 | 11.0 |
| Z4KE140A | 133 | 140 | 147 | 5.0 | 0.25 | 900 | 5500 | 0.5 | 100 | 106.4 | 1.0 | 10.7 |
| Z4KE150A | 142 | 150 | 158 | 5.0 | 0.25 | 1000 | 6000 | 0.5 | 100 | 113.6 | 1.0 | 10.0 |
| Z4KE160A | 152 | 160 | 168 | 5.0 | 0.25 | 1100 | 6500 | 0.5 | 100 | 121.6 | 1.0 | 9.0 |
| Z4KE170A | 162 | 170 | 179 | 5.0 | 0.25 | 1200 | 7000 | 0.5 | 100 | 129.6 | 1.0 | 8.0 |
| Z4KE180A | 171 | 180 | 189 | 5.0 | 0.25 | 1300 | 7000 | 0.5 | 100 | 136.8 | 1.0 | 8.0 |
| Z4KE190A | 180 | 190 | 200 | 5.0 | 0.25 | 1400 | 7500 | 0.5 | 100 | 144.0 | 1.0 | 7.9 |
| Z4KE200A | 190 | 200 | 210 | 5.0 | 0.25 | 1500 | 8000 | 0.5 | 100 | 152.0 | 1.0 | 7.0 |

Note

⁽¹⁾ Maximum power dissipation is 1500 mW at $T_L = 75\text{ }^\circ\text{C}$ with lead length 0.375" (9.5 mm)

| ORDERING INFORMATION (Example) | | | | |
|---------------------------------------|-----------------|------------------------|---------------|------------------------------------|
| PREFERRED P/N | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| Z4KE100A-E3/54 | 0.350 | 54 | 5500 | 13" diameter plastic tape and reel |
| Z4KE100AHE3/54 ⁽¹⁾ | 0.350 | 54 | 5500 | 13" diameter plastic tape and reel |

Note

⁽¹⁾ AEC-Q101 qualified

RATINGS AND CHARACTERISTICS CURVES

($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Fig. 1 - Power Derating Curve




Fig. 4 - Typical Reverse Characteristics




Fig. 2 - Typical Zener Impedance




Fig. 5 - Typical Temperature Coefficients




Fig. 3 - Typical Instantaneous Forward Characteristics





Fig. 6 - Typical Zener Voltage



PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

DO-204AL (DO-41)





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.