

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

| | |
|-----------------------------|---|
| Commercial Status | Commercialised |
| Range of product | Harmony XAC |
| Product or component type | Pendant control station |
| Control station name | XACA |
| Control station type | Double insulated |
| Enclosure material | Polypropylene |
| Electrical circuit type | Control circuit |
| Enclosure type | Complete ready for use |
| Control station application | Control of single speed hoist motor |
| Control station composition | 4 pushbuttons + 1 emergency stop |
| Control button type | Third pushbutton 1 NO right, slow Stop pushbutton Ø 40 mm 1 NC, latching Second pushbutton 1 NO lower, slow Fourth pushbutton 1 NO left, slow First pushbutton 1 NO raise, slow |
| Contact block name | ZB2BE102 for emergency stop ZB2BE101 for each direction |
| Mechanical interlocking | With mechanical interlocking between pairs |

Complementary

| | |
|---|---|
| Control station colour | Yellow |
| Connections - terminals | Screw clamp terminals, connection capacity: 1 x 0.5...2 x 1.5 mm ² with cable end Screw clamp terminals, connection capacity: 1 x 0.5...1 x 2.5 mm ² without cable end |
| Mechanical durability | 1000000 cycles |
| Cable entry | Rubber sleeve with stepped entry, cable outer diameter: 0.31...1.02 in (8...26 mm) |
| Contact code designation | Q600 DC-13, U _e = 600 V, I _e = 0.1 A conforming to IEC 60947-5-1 appendix A Q600 DC-13, U _e = 250 V, I _e = 0.27 A conforming to IEC 60947-5-1 appendix A A600 AC-15, U _e = 600 V, I _e = 1.2 A conforming to IEC 60947-5-1 appendix A A600 AC-15, U _e = 240 V, I _e = 3 A conforming to IEC 60947-5-1 appendix A |
| [I _{th} e] conventional enclosed thermal current | 10 A |
| [U _i] rated insulation voltage | 600 V (degree of pollution: 3) |
| [U _{imp}] rated impulse withstand voltage | 6 kV conforming to IEC 60947-1 |
| Contacts operation | Slow-break |
| Resistance across terminals | <= 25 MOhm |
| Operating force | 8 N for emergency stop 10 N for pushbutton |
| Short circuit protection | 10 A fuse protection by cartridge fuse type gG |
| Rated operational power in W | 65 W DC-13 for 1000000 cycles, operating rate = 60 cyc/mn at 24 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C 48 W DC-13 for 1000000 cycles, operating rate = 60 cyc/mn at 48 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C 40 W DC-13 for 1000000 cycles, operating rate = 60 cyc/mn at 120 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C |
| Terminals description ISO n°1 | (13-14)NO |
| Terminals description ISO n°2 | (11-12)NC |
| Terminal identifier | (11-12)NC (13-14)NO |
| Product weight | 1.76 lb(US) (0.8 kg) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|--|--|
| Standards | EN/IEC 60204-32 EN/IEC 60947-5-1 UL 508 CSA C22.2 No 14 |
| Product certifications | CCC GOST |
| Protective treatment | TH |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 15 gn (f = 10...500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 100 gn conforming to IEC 60068-2-27 |
| Class of protection against electric shock | Class II |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 50102 |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 18407 - WORLD SERVICE PARTS(SENSORS) |
| Discount Schedule | T |
| GTIN | 00785901277934 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 2.10 |
| Product availability | Non-Stock - Not normally stocked in distribution facility |
| Returnability | N |
| Country of origin | CZ |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|