

INSTA CONTACTOR WITH 2 NO CONTACTS CONTACT FOR AC
230, 400V 20A ACTIVATION ACDC24V



| Model | |
|--|------------------|
| Product brand name | SETRON |
| Product designation | Insta contactors |
| Design of the product | 2 NO contacts |
| Type of voltage / of the operating voltage | AC |
| Type of voltage / for actuation | AC/DC |
| Protection class | |
| Protection class IP | IP20 |
| Dissipation | |
| Power loss [W] | 1.7 W |
| <ul style="list-style-type: none"> for rated value of the current / at AC / in hot operating state / per pole | 1.7 W |
| <ul style="list-style-type: none"> maximum | 1.7 W |
| Main circuit | |
| Operating voltage / rated value | 230 V |
| <ul style="list-style-type: none"> minimum | 230 V |
| <ul style="list-style-type: none"> maximum | 230 V |
| Operating current / rated value | 20 A |

Control current

Control supply voltage

- | | |
|-------------------------|------|
| • rated value | 24 V |
| • rated value / maximum | 24 V |
| • at DC / rated value | 24 V |

Product details

| | |
|--|-----|
| Product component / Slide for manual operation | No |
| Product extension / can be installed / supplementary devices | Yes |

Number

| | |
|-----------------------|---|
| Number of NC contacts | 0 |
| Number of NO contacts | 2 |

Mechanical Design

| | |
|-----------------------|---------|
| Height | 90 mm |
| Width | 17.5 mm |
| Depth | 71 mm |
| Installation depth | 64 mm |
| Number of width units | 1 |
| Net weight | 141 g |

Certificates

| | |
|--|---|
| Equipment marking / acc. to DIN EN 61346-2 | Q |
|--|---|

General Product Approval

Declaration of Conformity



[Miscellaneous](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT5000-2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT5000-2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT5000-2

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



