






		Conditions	
cell type:	NiMH		
cell size:	AA		
nominal voltage:	1.2 V		
max. charge voltage:	1.5 V	at standard charge (0.1C / 20°C)	
capacity			
nominal:	2850 mAh	discharge at 0.2C	
minimum:	2650 mAh	discharge at 0.2C	
	2450 mAh	discharge at 1C	
		1.0V end discharge voltage	
		ta: 20°C	
max. continuous discharge current:	5000 mA	ta: 0...45°C	
charge		current	time
standard charge:	285 mA	800 mA	14....16hrs
quick charge:	800 mA	2850 mA	4hrs
fast charge:	2850 mA		1hr
recommended charge termination control parameters:	0...5 mV	- ΔV (-deltaV)	
	0.8...1 °C	temperature rise per minute	
	45...50 °C	TCO (temperature cut off)	
trickle charge current:	20...80 mA	(recommended)	
continuous overcharge: (less than 1 year)	≤ 200 mA	no conspicuous deformation no leakage	
internal resistance: (impedance)	≤ 30 mΩ	at 1KHz battery fully charged	
life expectancy:	≥ 500 cycles	acc. IEC standard	
self discharge			
charge retention:	≥ 60 %	after 28 days storage at 20°C	
initial capacity:	≥ 900 mAh	within 30 days after delivery discharge at 0.2C	
ambient temperature range:	0...45 °C	standard charge	
	10...40 °C	fast charge	
	- 20...65 °C	discharge	
	- 20...50 °C	storage (≤1month)	
	- 20...40 °C	storage (≤3months)	
	- 20...30 °C	storage (≤12months)	
QCT1:	20/2500/35		
QCT2:	30/2350/40		

Diagrams



mechanical specifications

cell dimensions			
diameter d1:		14.5 - 0.7	mm
diameter d2:	max.	5.5	mm
height h1:		50.5 - 0.5	mm
height h2:	min.	1.2	mm
weight:		31 ± 2	g



	ANSMANN Specifications for model:	NiMH Battery AA - 2850mAh
	data sheet no. / part no.	
	supplier no.	702069
	author / date	TG / 24.07.2018